PAB PERIMETRAL ADVERTISING BOARD PRODUCTS – January 2009

This product's list cancels and replaces any previous release. In order to improve products and technology continuously and meet the requirements of an ever evolving marketplace, the manufacturer reserves the right to modify the below contents at any moment without prior notice.

MODEL	PAB SP	PAB TL	PAB TLH	PAB TLH+
Use	Outdoor	Indoor/Outdoor	Indoor / Outdoor	Indoor / Outdoor
LEDs per Pixel	2R, 1G, 1B	1 Top LED RGB	1 Top LED RGB	1 Top LED RGB
Horizontal Physical Pitch – mm	27,5	20,50	20,50	20,50
Vertical Physical Pitch – mm	27,5	15,625	15,625	15,625
Visible Pitch - mm	13.75	-	-	-
Panel Size – mm	2640x880x160	2624x750x120	2624x875x120	2624x1000x120
Panel Graphic Definition	96x32	128x48	128x56	128x64
Horizontal Viewing Angle	160°	160°	160°	160°
Vertical Viewing Angle	60°	120°	120°	120°
Resolution – Px/sqm	1.322	3.122	3.122	3.122
Brightness – NIT	~6.500	~5.500	~5.500	~5.500
Refresh Rate – Hz	1.000	1.000	1.000	1.000
Medium Consumption – Kw/Panel	0,45	0,72	0,84	0,96
Weight – Kg./Panel	75	65	75	85

Note: with the horizontal and vertical numbers of the screen type panels, you can create the screen sizes, which meet your request.

ELECTRONIC CONTROL SYSTEM FOR PERIMETRAL ADVERTISING BOARD

DLX Banner or DLX Banner-Plus

ACCESSORIES		
Spare Parts KIT	Flight Case	
DLX Pro-II	Fiber Optic	
PAB Battery	RJ2bnc-2 Converter	
Power Box	RJ2bnc-2 Converter (80m)	
Rubber for top protection & stabilizing Feet	RJ2bnc-2 Converter (200m)	